

Puck Oxygen Optode



The Puck Oxygen Optode 5730 is a compact sensor intended for OEM integration. It is measuring O₂ concentration and temperature.

Advantages


- Optical
- Long time stability
- Stable and rugged foil. No foil change necessary
- Low maintenance needs
- Not stirring sensitive (it consumes no oxygen)
- Presenting calibrated data directly
- Compact sensor for OEM integration
- Output format: RS-232

Since oxygen is involved in most of the biological and chemical processes in aquatic environments and in the process industry, it is one of the most important parameters to be measured. Aanderaa revolutionized oceanographic oxygen monitoring/research with the introduction of oxygen optodes in 2002. Applications range from shallow creeks to the deepest trenches, from tropical to in-ice/in-sediment measurements. More than 200 scientific papers have so far been published using Aanderaa Optodes.

Specifications PUCK OXYGEN OPTODE 5730



Pin Configuration Molex



- 1: VPWR
- 2: GND
- 3: TXD
- 4: RXD
- 5: Boot Enable

Foil Service Kit 5731



Misleading specifications

When Aanderaa states an absolute accuracy of e.g. ($\pm 2\%$ or $\pm 4 \mu\text{M}$) we mean the accuracy of the sensor in the field over the entire range of oxygen concentrations and temperatures, others might refer to accuracy in the laboratory just after the sensor was calibrated. When Aanderaa give response time in water others might refer to response time in air which is much faster. For more information read our [Best Practice document](#) on Oxygen Optodes.

Technical Details		
Oxygen:	O₂ Concentration	Air Saturation
Measurement Range:	0 - 1000 μM or 0-32 mg/L	0 - 300%
Calibration method:	40-point automatic calibration, 20-point verification, 3 fully Winkler calibrated optodes for referencing Stable and rugged FDO701 foil.	
Sensing Foils:		
Calibration Range:	0 - 500 μM ¹⁾ or 0-16 mg/L	0 - 120%
Resolution:	< 0.1 μM or 0.032 mg/L	0.05 %
Accuracy:	< 4 μM ²⁾ or 0.128 mg/L	< 2 % ³⁾
Response Time (63%):	< 30 sec	
Typical field drift:	< 0.5 % per year	
Foil Lifetime:	+10 years, do not change foil unless mechanically damaged.	
Temperature:		
Range:	-5 to +40°C (23-104°F)	
Resolution:	0.01°C (0.018°F)	
Accuracy:	$\pm 0.03^\circ\text{C}$ (0.054°F) ⁴⁾	
Response Time (63%):	< 2 sec	
Typical field drift:	< 0.01 degC per year	
Output format:	RS-232	
Output Parameters:	O ₂ concentration in μM and mg/L, Air Saturation in %, temperature in °C, Oxygen raw data and temperature raw data	
Sampling interval:	1 sec - 255 min	
Supply voltage:	5 to 14Vdc	
Current drain⁵⁾:		
Average:		
Model 5730:	0.16 +48mA/S	
Maximum:	100 mA	
Quiescent:		
Model 5730:	0.16mA	
Operating depth:	0-100 m (0-328ft)	
Electrical connection:	Molex 5pin 1.25mm Pitch Pico Blade Header	
Dimension (WxDxH):	Ø39.1 x 35.8mm (Ø1.54"x 1.41")	
Weight:	43g (1.52oz)	
Materials:	POM, PA, Titanium	
Accessories:	Foil Service Kit 5731	

⁽¹⁾ other ranges available on request

⁽²⁾ requires salinity compensation for salinity variations > 1mS/cm, and pressure compensation for pressure > 100meter

⁽³⁾ within calibrated range 0 - 120% / 0 - 30°C

⁽⁴⁾ within calibrated range 0 - 30°C

⁽⁵⁾ at 5V power

Specifications subject to change without prior notice.

Aanderaa Data Instruments AS

Sanddalsringen 5b

P.O. Box 103 Midtun

5843 Bergen, Norway

+47 55 60 48 00

aanderaa.info@xyleminc.com

Aanderaa.com



Aanderaa.com/URL